



TIN OAK

Tin Oak is agrey stained 1-strip with a rustic look. May contain knots and small cracks.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	101P6FEK0GKW120 / 7393969037617
Design / Wood Species	Plank / White Oak
Surface Treatment / Natural/Stained	Matte finish / Stained
Refining Treatment	Beveled 4-sided
Width x Length x Thickness	4 7/8 x 47 1/4 x 3/8"
Weight per package / per m2	30.9 lbs / 20.6 lbs
Area per package	16.1 sqft
Grading	Lively
Joint	Woodloc®
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	1 time
Core material	HDF
Backside material	Veneer

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m ³		>800 kg/m ³
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.07 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kährs.com | ©Kährs,
USA & Canada 2026-04-11

