



## OAK NOUVEAU TAUPE

The grey-stain found on this single-strip oak floor from the Classic Nouveau Collection enhance the earth undertones and balance the natural contrasts in the wood. Knots and cracks lightly pepper the boards, adding subtle depth to the floor's elegant expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

### PRODUCT DETAILS

<b>Article Number</b>	151N9AEK18KW200
<b>EAN Code</b>	7393969046435
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Brushed, Microbeveled 4-sided
<b>Dimensions</b>	7 3/8 x 78 3/4 "
<b>Weight per Package</b>	39.7 lbs
<b>Area per Package</b>	23.7 sqft
<b>Area per pallet</b>	1085 sqft
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Lively
<b>Range</b>	Kährs Original
<b>Collection</b>	Classic Nouveau Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Warranty</b>	25 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Backside material</b>	Spruce
<b>Thickness</b>	5/8"
<b>Installation method</b>	Floating, Glue-Down
<b>Surface Color</b>	Grey

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slipperiness</b>	CEN/TS15676	NPD


## Other products in this collection



Oak Nouveau Taupe



Oak Nouveau Whisper



Oak Nouveau Lace



Oak Nouveau Blonde



Oak Nouveau Gray




Oak Nouveau Greige



Oak Nouveau White



Oak Nouveau Snow



Oak Nouveau Black

## CERTIFICATES



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*