



OAK CREME

Creme has a distinct white hue on a naturally color varying oak. The surface is brushed and matt laquered.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Flooring / 3-layer engineered	LRV / LRV Std1
Article Number / EAN Code	152N7BEK0WKW240 / 7393969037464	Warranty
Design / Wood Species	2-strip / White Oak	— TECHNICAL PROPERTIES
Surface Treatment /	Matte finish / Stained	Moisture content
Natural/Stained		
Refining Treatment	Brushed	—— Minimun Mean Density —— kg/m³
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"	— Reaction To Fire
Weight per package / per	50.7 lbs / 17.4 lbs	Formaldehyde Emission
m2		— Content PCP
Area per package / per	31.3 sqft / 1409.5 sqft	
pallet		Breaking Strength N/mm²
Grading	Variation	Thermal Resistance R-Value
loint	Woodloc® 5S	— Biological Durability
Installation method	Floating, Glue-Down	CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 1/8"	TSCA de SWAN EQ MUSSION CLAS
thickness		CARB P2
Resandable	2 times	Compliant Page of the Compliant
Core material	Pine/Spruce/Alder	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

LRV / LRV Std1	58 / 3.7	
Warranty	25 years	
- TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
- Minimun Mean Density		>500 kg/m³
- kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
- Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD









CEN/TS15676

EN350-2



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

.11 (m2K/W)

Class 1

NPD

Compliant

Other products in this collection







Oak Pale

Oak Limestone