



# OAK CREME

Creme has a distinct white hue on a naturally color varying oak. The surface is brushed and matt laquered.

| PRODUCT DETAILS   |   | FACTS                |                     | TECHNICAL PROPERTIES       |             |             |
|---|---|----------------------|---------------------|----------------------------|-------------|-------------|
| Article Number  | 152N7BEK0WKW240                             | Wood Species         | White Oak           | Moisture content           | EN13183     | 7%±2%       |
| EAN Code  | 7393969037464                               | Design               | 2-strip             | Minimum Mean Density kg/m³ |             |             |
| Surface Treatment   | Matte finish                                | Grading              | Variation           | >500 kg/m³                 |             |             |
| Refining Treatment  | Brushed                                     | Range                | Kährs Original      | Reaction To Fire           | EN13501-1   | Dfl-s1      |
| Dimensions  | 7 7/8 x 95 3/8 "                            | Collection           | Harmony Collection  | Formaldehyde Emission      | EN717-1     | E1          |
| Weight per Package  | 50.7 lbs                                    | Resandable           | 2 times             | Content PCP                | CEN/TR14823 | ≤ 5 x 10-6n |
| Area per Package  | 31.2 sqft                                   | Natural/Stained      | Stained             | Breaking Strength N/mm²    | EN1533      | NPD         |
| Package info  | Packages may contain start and stop boards. | Brinell Value        | 3,7                 | Thermal Conductivity       | EN12664     | 0,14 W/mK   |
| DETAIL DESCRIPTION  |   | Joint                | Woodloc® 5S         | Thermal Resistance R-Value | .11 (m2K/W) |             |
| Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers. |   | Floor heating        | Yes                 | Biological Durability      | EN350-2     | Class 1     |
|   |   | Warranty             | 30 years            | CARB2                      | Compliant   |             |
|   |   | Warranty             | 25 years            | Slipperiness               | CEN/TS15676 | NPD         |
| COLOR CHANGE  |   | Wear-layer material  | Hardwood            |                            |             |             |
| Stained product - noticable color change over time.   |   | Wear Layer Thickness | 1/8"                |                            |             |             |
|   |   | Core material        | Pine/Spruce lamella |                            |             |             |
|   |   | Thickness            | 5/8"                |                            |             |             |
|   |   | Installation method  | Floating, Glue-Down |                            |             |             |

Other products in this collection



Alloy



Pale



Oak Creme



Oak Granite



Oak Cirrus



Oak Limestone



Oak Lava

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*