

## OAK BERLIN

The lightly smoked finish in this exclusive, single-strip oak floor from the Capital Collection beautifully balances its soft grey and pale ash colour palette. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel.

| PRODUCT DETAILS             |  | PRODUCT DETAILS                       |                      |                              |
|-----------------------------|--|---------------------------------------|----------------------|------------------------------|
| Product type / Construction | Wood Floors / 3-layer parquet                | LRV / LRV Std1                        | 24 / 2.9             |                              |
| Article Number / EAN Code   | 151N4AEKFMKW220 / 7393969041133              | Warranty                              | 30 years             |                              |
| Design / Wood Species       | 1-strip / Oak                                | TECHNICAL PROPERTIES                  |                      |                              |
| Surface treatment /         | Oil / Stained                                | Moisture content                      | EN13183              | 7%±2%                        |
| Natural/Stained             |  |                                       | LINISTOS             |                              |
| Design features             | Microbevelled 4-sided, Brushed, Light smoked | Minimun Mean Density                  |                      | >500 kg/m³                   |
| Width x Length x Thickness  | 187 x 2266 x 15 mm                           | kg/m <sup>3</sup><br>Reaction To Fire | EN13501-1            | Dfl-s1                       |
| Weight per package / per    | 21 kg / 8.4 kg                               |                                       | EN13301-1<br>EN717-1 | F1                           |
| m2                          |  | Formaldehyde Emission                 |                      |                              |
| Area per package / per      | 2.5 m <sup>2</sup> / 114.3 m <sup>2</sup>    | Content PCP                           | CEN/TR14823          | ≤ 5 ppm                      |
| pallet                      |  | Breaking Strength N/mm <sup>2</sup>   | EN1533               | NPD                          |
| Grading                     | Calm   | Thermal Conductivity                  | EN12664              | 0,11W/mK                     |
| loint                       | Woodloc® 5S                                  | Thermal Resistance R-Value            |                      | .11 (m2K/W)                  |
|                             |  | Biological Durability                 | EN350-2              | Class 1                      |
| Installation method         | Floating, Glue-down                          | CARB2                                 |                      | Compliant                    |
| Floor heating               | Yes  | Slip resistance                       | CEN/TS15676          | NPD                          |
| Wear leayer material /      | Hardwood / 3.5 mm                            |                                       | CENTOTOOTO           |                              |
| thickness                   |  |                                       | ethission class      | (ORDERING DANS LAW RETINKEN) |
| Resandable                  | 2-3 times                                    |                                       |                      |                              |
| Core material               | Pine/Spruce lamella                          | Compliant SundaHu                     |                      |                              |
| Hardness (Brinell) value /  | 3,7 / 2.2 - 5.9                              | floor <b>C</b>                        |                      |                              |
| range                       |  |                                       |                      |                              |

## DETAILED DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

SITIALI SIZEU KITOLS ITI IITILEU TUTTDELS AllOWEU.

**Oil:** This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Descriptions & Imagery

www.kahrs.com | <sup>©</sup>Kährs 2025-07-03

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection



OAK DUBLIN ULTRA MATT







OAK DUBLIN ULTRA MATT NARROW



OAK PARIS OILED



OAK PARIS ULTRA MATT NARROW / HONEY OAT



OAK DUBLIN OILED

OAK PRAGUE

OAK BERLIN