



OAK DUBLIN OILED 242

The light honey nuances in this exclusive, single-strip oak floor from the Capital Collection range from faint tan to pale golden brown, resulting in an even expression overall. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 151N4AEKF0KW240 / 7393969037525 |
| Design / Wood Species | Plank / Oak |
| Surface treatment / Natural/Stained | Oil / Natural |
| Design features | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness | 187 x 2420 x 15 mm |
| Weight per package / per m2 | 22 kg / 8.15 kg |
| Area per package / per pallet | 2.72 m ² / 122.4 m ² |
| Grading | Calm |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | |
|----------|----------|
| Warranty | 30 years |
|----------|----------|

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | | >500 kg/m ³ |
| kg/m ³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK DUBLIN ULTRA MATT



OAK PARIS ULTRA MATT



OAK DUBLIN ULTRA MATT
NARROW



OAK PARIS ULTRA MATT
NARROW



OAK PRAGUE



OAK BERLIN



OAK PARIS OILED



OAK DUBLIN OILED