



OAK DUBLIN

brown.

The light honey nuances in this exclusive, single-strip oak floor from the Capital Collection range from faint tan to pale golden brown, resulting in an even expression overall. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------|---------------------|-------------------------------------------------------------|-------------|------------------------|
| Article Number | 151N4AEKF0KW240 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969037525 | Design | 1-strip | content | | |
| Surface treatment | Oil This floor should be oiled immediately after installation. | Grading | Calm | Minimun Mean Density kg/m³ > Reaction To EN13501-1 E Fire | | >500 kg/m ³ |
| | | Range | Kährs Original | | | Dfl-s1 |
| | | Collection | Capital Collection | Formaldehyde | EN717-1 | E1 |
| Design features | Microbevelled 4-sided | Resandable | 2-3 times | Emission | | |
| Dimensions | 187 x 2420 mm | Natural/Stained | Natural | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Weight per Package | 22 kg | Brinell Value | 3,7 | Breaking | EN1533 | NPD |
| Area per Package | 2.7 m ² | Joint | Woodloc® 5S | Strength N/mm ² | | |
| Area per pallet | 122.4 m ² | Floor heating | Yes | Thermal | EN12664 | 0,14 W/mK |
| Package info | Packages may contain start and stop boards. | Warranty | 30 years | Conductivity | | |
| | | Warranty US | 25 years | Thermal Resistance R-Value | | .11 (m2K/W) |
| DETAIL DESCRIPTION | | Wear-layer material | Hardwood | Biological Durability | EN350-2 | Class 1 |
| Even colour with minor variations. Small sized knots in limited numbers allowed. COLOUR CHANGE | | Wear Layer Thickness | 3.5 mm | CARB2 | | Compliant |
| | | Core material | Pine/Spruce lamella | Slipperiness CEN/TS15676 | | ' |
| | | Thickness | 15 mm | | 22 313070 | |
| Some muting of colour variation to medium, straw | | Installation method | Floating, Glue-down | | | |

Other products in this collection









Oak Prague Oak Berlin Oak Paris Oak Dublin

CERTIFICATES

















Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.