



# OAK NOUVEAU INK

Deep and dark tones with a warm glow underneath creates a robust and full-bodied atmosphere.

| PRODUCT DETAILS                                      |   | FACTS                |                            | TECHNICAL PROPERTIES                  |             |             |
|--|---|----------------------|----------------------------|---------------------------------------|-------------|-------------|
| Article Number                                       | 151N9AEK19KW200   | Wood Species         | Oak                        | Moisture content                      | EN13183     | 7%±2%       |
| EAN Code   | 7393969046442   | Design               | 1-strip                    | Minimum Mean Density kg/m³ >500 kg/m³ |             |             |
| Surface Treatment                                    | Matt lacquer  | Grading              | Lively                     | Reaction To Fire                      | EN13501-1   | Dfl-s1      |
| Refining Treatment                                   | Brushed, Microbevelled 4-sided  | Range                | Kährs Original             | Formaldehyde Emission                 | EN717-1     | E1          |
| Dimensions   | 187 x 2000 mm   | Collection           | Classic Nouveau Collection | Content PCP                           | CEN/TR14823 | ≤ 5 x 10-6n |
| Weight per Package                                   | 18 kg   | Natural/Stained      | Stained                    | Breaking Strength N/mm²               | EN1533      | NPD         |
| Area per Package                                     | 2.2 m²  | Brinell Value        | 3,7                        | Thermal Conductivity                  | EN12664     | 0,14 W/mK   |
| Area per pallet                                      | 100.8 m²  | Joint                | Woodloc® 5S                | Thermal Resistance R-Value            | .11 (m2K/W) |             |
| Package info   | Packages may contain start and stop boards.   | Floor heating        | Yes                        | Biological Durability                 | EN350-2     | Class 1     |
|  |   |                      | 25 years                   | CARB2                                 | Compliant   |             |
|  |   | Wear-layer material  | Hardwood                   | Slipperiness                          | CEN/TS15676 | NPD         |
|  |   | Wear Layer Thickness | 3.5 mm                     |                                       |             |             |
|  |   | Core material        | Pine/Spruce lamella        |                                       |             |             |
| DETAIL DESCRIPTION                                   | All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | Backside material    | Spruce                     |                                       |             |             |
|  |   |                      | 15 mm                      |                                       |             |             |
|  |   | Installation method  | Floating, Glue-down        |                                       |             |             |
| COLOUR CHANGE  |   | Surface Colour       | Dark brown                 |                                       |             |             |
| Stained product - noticeable color change over time. |   |                      |                            |                                       |             |             |

Other products in this collection



Oak Nouveau Lace



Oak Nouveau Rich



Oak Nouveau Blonde



Oak Nouveau Gray



Oak Nouveau Tawny



Oak Nouveau Greige



Oak Nouveau White



Oak Nouveau Snow



Oak Nouveau Black

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.