

STUDIO OAK CD 11 MM

Oak CD is a colorful oak floor with both color variations and knots.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--------------------|--|----------------------|-------------------|---|----------------------------|---------------|
| Article Number | 111PCDEK09KH050 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969046022 | Design | Pattern | content | | |
| Surface Treatment | Matt lacquer | Grading | Lively | Minimun Mean Density kg/m ³ >500 kg/m ³ | | |
| Dimensions | 70 x 490 mm | Range | Kährs Master | Reaction To Fire | EN13501-1 | Cfl-s1 |
| Weight per Package | 13.3 kg | Collection | Studio Collection | Formaldehyde Emission | EN717-1 | E1 |
| Area per Package | 2.1 m ² | Natural/Stained | Natural | | | |
| Package info | Packages may contain start and stop boards. | Brinell Value | 3,7 | Content PCP CEN/TR14823 ≤ 5 | | 3 ≤ 5 x 10-6n |
| | | Joint | Tongue & Groove | Breaking Strength N/mm² | EN1533 | NPD |
| | | Wear-layer material | Hardwood | | | |
| | | Wear Layer Thickness | 4 mm | Thermal | EN12664 | 0,14 W/mK |
| | | Core material | Birch Plywood | Conductivity | | |
| | | | 11 mm | Thermal Resista | Thermal Resistance R-Value | |
| | | Installation method | Glue-down | Biological Durability | EN350-2 | Class 1 |
| | | | | CARB2 | | Compliant |
| | | | | Slipperiness | CEN/TS15676 | 5 NPD |

Other products in this collection





mm

Studio Oak AB White 11 mm

noked Oak AB 11



Studio Oak AB 11 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.