



OAK PORDOI

The warm earthy tones in this single-strip oak floor from the Rifugio Collection are enhanced by a natural oil finish, which highlights the charcoal knots and cracks. Each board is carefully brushed to bring out the character of the grain and emphasises the natural texture of the wood. Four-sided jagged bevelling at the edges and saw marks enhances the worn appearance of the floor.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	151XDDEKF6KW195 / 7393969046541
Design / Wood Species	1-strip / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Broken bevelled 4-sided, Brushed, Smoked, Saw marks
Width x Length x Thickness	190 x 1900 x 15 mm
Weight per package / per m2	16.7 kg / 7.59 kg
Area per package / per pallet	2.17 m² / 75.95 m²
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9

PRODUCT DETAILS		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density	kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK COMICI