



OAK PORDOI

The warm earthy tones in this single-strip oak floor from the Rifugio Collection are enhanced by a natural oil finish, which highlights the charcoal knots and cracks. Each board is carefully brushed to bring out the character of the grain and emphasises the natural texture of the wood. Four-sided jagged bevelling at the edges and saw marks enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Warranty	30 years
Article Number / EAN Code	151XDDEKF6KW195 / 7393969046541	TECHNICAL PROPERTIES	
Design / Wood Species	Plank / Oak	Moisture content	EN13183 7%±2%
Surface treatment / Natural/Stained	Oil / Stained	Minimum Mean Density	>500 kg/m³
Design features	Broken bevelled 4-sided, Brushed, Smoked, Saw marks	Reaction To Fire	EN13501-1 Dfl-s1
Width x Length x Thickness	190 x 1900 x 15 mm	Formaldehyde Emission	EN717-1 E1
Weight per package / per m2	16.7 kg / 7.59 kg	Content PCP	CEN/TR14823 ≤ 5 ppm
Area per package / per pallet	2.17 m² / 75.95 m²	Breaking Strength N/mm²	EN1533 NPD
Grading	Dynamic	Thermal Conductivity	EN12664 0,11W/mK
Joint	Woodloc® 5G	Biological Durability	EN350-2 Class 1
Installation method	Floating, Glue-down	CARB2	Compliant
Floor heating	Yes	Slip resistance	CEN/TS15676 NPD
Wear leayer material / thickness	Hardwood / 3.5 mm		
Resandable	2-3 times		
Core material	Pine/Spruce		
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9		

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

