



OAK OYSTER

The blached white finish on this single-strip oak floor from the Artisan Collection balances the naturally occurring colour variations, which range from heather grey to faded silver lavender, for a refined yet rustic effect. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 151XCDEKFVKW195 / 7393969045285 |
| Design / Wood Species | Plank / Oak |
| Surface treatment / Natural/Stained | Oil / Stained |
| Design features | Bevelled 4-sided, Brushed, Handscraped |
| Width x Length x Thickness | 190 x 1900 x 15 mm |
| Weight per package / per m2 | 17 kg / 7.73 kg |
| Area per package / per pallet | 2.17 m² / 75.95 m² |
| Grading | Dynamic |
| Joint | Woodloc® 5G |
| Installation method | Glue-down, Floating |
| Floor heating | Yes |
| Wear leayer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------|-------------|------------|
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK BUCKSKIN



MAPLE CAROB



OAK CONCRETE



OAK STRAW



OAK OYSTER



OAK EARTH



OAK CAMINO