



OAK OYSTER

A rustic, hand scraped product. White coloured and natural oil. the boards may contain large knots and cracks.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151XCDEKFKW195	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969045285	Design	1-strip	Minimum Mean Density kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Refining Treatment	Bevelled 4-sided, Brushed, Handscraped	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Dimensions	190 x 1900 mm	Collection	Artisan Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	17 kg	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area per Package	2.2 m²	Joint	Woodloc® 5G	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION			25 years	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Wear Layer Thickness	3.5 mm	Slipperiness	CEN/TS15676	NPD
		Core material	Pine/Spruce lamella			
			15 mm			
		Installation method	Glue-down, Floating			
		Surface Colour	White			

COLOUR CHANGE

Stained product - noticable color change over time.

Other products in this collection



Oak Concrete



Oak Tan



Oak Straw



Oak Oyster



Oak Linen



Oak Earth



Oak Camino

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.