



OAK OYSTER

A rustic, hand scraped product. White coloured and natural oil. the boards may contain large knots and cracks. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151XCDEKFKW195	Wood Species	White Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969045285	Design	1-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Refining Treatment	Beveled 4-sided, Brushed, Handscraped	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Dimensions	7 1/2 x 74 3/4 "	Collection	Artisan Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	37.5 lbs	Resandable	2 times	Breaking Strength N/mm²	EN1533	NPD
Area per Package	23.7 sqft	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5G	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Warranty	30 years	CARB2		Compliant
		Warranty	25 years	Slipperiness	CEN/TS15676	NPD
		Wear-layer material	Hardwood			
		Wear Layer Thickness	1/8"			
		Core material	Pine/Spruce lamella			
		Thickness	5/8"			
		Installation method	Glue-Down, Floating			
		Surface Color	White			

COLOR CHANGE

Stained product - noticable color change over time.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.