



# OAK TAN

The lightly smoked finish on this single-strip oak floor from the Artisan Collection balances the warm turmeric nuances. Naturally occurring knots and cracks pepper the boards, adding depth and bringing life to the floor's rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 3-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	151XCDEKFSKW195 / 7393969045308	Minimum Mean Density	>500 kg/m³	
Design / Wood Species	1-strip / Oak	kg/m³		
Surface treatment / Natural/Stained	Oil / Natural	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Bevelled 4-sided, Brushed, Light smoked, Handscraped	Formaldehyde Emission	EN717-1	E1
Width x Length x Thickness	190 x 1900 x 15 mm	Content PCP	CEN/TR14823	≤ 5 ppm
Weight per package / per m2	17 kg / 7.73 kg	Breaking Strength N/mm²	EN1533	NPD
Area per package / per pallet	2.17 m² / 75.95 m²	Thermal Conductivity	EN12664	0,11W/mK
Grading	Dynamic	Thermal Resistance R-Value	.11 (m2K/W)	
Joint	Woodloc® 5G	Biological Durability	EN350-2	Class 1
Installation method	Floating, Glue-down	CARB2	Compliant	
Floor heating	Yes	Slip resistance	CEN/TS15676	NPD
Wear leayer material / thickness	Hardwood / 3.5 mm	<div><div><div>TSCA TITLE VI &amp; CARB P2 Compliant</div><div><div>BASTA</div></div><div><div>CE</div></div><div><div><div>ENVIRONMENTAL LABELLING INFORMATION</div><div>A M L C</div></div></div></div></div>		
Resandable	2-3 times			
Core material	Pine/Spruce lamella			
Warranty	30 years			

## DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Smoked product - noticable color change over time.
- Packages may contain start and stop boards.

Other products in this collection



OAK BUCKSKIN



MAPLE CAROB



OAK CONCRETE



OAK STRAW



OAK OYSTER



OAK EARTH



OAK CAMINO