



OAK TAN

A rustic, handscraped product. Light Smoked which gives it a darker impression.

PRODUCT DETAILS Product type / Construction Wood Flooring / 3-layer parquet Article Number / EAN Code 151XCDEKFSKW195 / 7393969045308 Design / Wood Species 1-strip / Oak Surface Treatment / Oil / Natural Natural/Stained Bevelled 4-sided, Brushed, Light smoked, **Refining Treatment** Handscraped Width x Length x Thickness 190 x 1900 x 15 mm Weight per package / per 17 kg / 7.73 kg m2 Area per package / per 2.17 m² / 75.95 m² pallet Grading Dynamic Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times

Pine/Spruce lamella

30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

Core material

Warranty

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection







OAK CONCRETE



OAK STRAW



OAK OYSTER







OAK CAMINO