



Da Capo Collection



OAK INDIETRO

This smoked, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from bleached blonde to rich carob hues to create a dramatic and weathered look. The knots, cracks and discolourations in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS

| | |
|-----------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 153XCDEKRNKW195 / 7393969045476 |
| Design / Wood Species | 3-strip / Oak |
| Surface treatment / | Oil / Natural |
| Natural/Stained | |
| Design features | Brushed, Saw marks, Smoked |
| Width x Length x Thickness | 190 x 1900 x 15 mm |
| Weight per package / per | 19 kg / 8.64 kg |
| m2 | |
| Area per package / per | 2.17 m ² / 75.95 m ² |
| pallet | |
| Grading | Expressive |
| Joint | Woodloc® 5G |
| Installation method | Glue-down, Floating |
| Floor heating | Yes |
| Wear leayer material / | Hardwood / 3.5 mm |
| thickness | |
| Resandable | 2-4 times |
| Core material | Pine/Spruce |
| Backside material | Veneer |

PRODUCT DETAILS

| | |
|----------------------------|-----------------|
| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 |
| range | |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | | >500 kg/m ³ |
| kg/m ³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-01-11

Other products in this collection



OAK INDIETRO



OAK DECORUM



OAK DOMO



OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE