



# OAK INDIETRO

This smoked, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from bleached blonde to rich carob hues to create a dramatic and weathered look. The knots, cracks and discolourations in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DETAILS  |   | FACTS                |                     | TECHNICAL PROPERTIES                    |                        |             |
|--|---|----------------------|---------------------|---|------------------------|-------------|
| Article Number   | 153XCDEKRNKW195   | Wood Species         | Oak                 | Moisture                                | EN13183                | 7%±2%       |
| EAN Code   | 7393969045476   | Design               | 3-strip             | content                                 |                        |             |
| Surface Treatment  | Oil<br>This floor should be oiled<br>immediately after<br>installation. | Grading              | Expressive          | Minimun Mean                            | >500 kg/m <sup>3</sup> |             |
|  |   | Range                | Kährs Supreme       | Reaction To<br>Fire                     | EN13501-1              | Dfl-s1      |
|  |   | Collection           | Da Capo Collection  | Formaldehyde<br>Emission<br>Content PCP | EN717-1                | E1          |
| Refining Treatment   | Brushed, Saw marks,   | Natural/Stained      | Natural             |   |                        |             |
|  | Smoked  | Brinell Value        | 3,7                 |   | CEN/TR14823            | ≤ 5 x 10-6n |
| Dimensions   | 190 x 1900 mm   | Joint                | Woodloc® 5G         | Breaking<br>Strength<br>N/mm²           | EN1533                 | NPD         |
| Weight per Package   | 19 kg   | Floor heating        | Yes                 |   |                        |             |
| Area per Package   | 2.2 m <sup>2</sup>  | rioor neating        |                     |   |                        |             |
| Area per pallet  | 76 m²   |                      | 25 years            | Thermal                                 | EN12664                | 0,14 W/mK   |
|  |   | Wear-layer material  | Hardwood            | Conductivity                            |                        |             |
| Package info   | Packages may contain start and stop boards.                             | Wear Layer Thickness | 3.5 mm              | Thermal Resistance R-Value              |                        | .11 (m2K/W) |
|  |   | Core material        | Pine/Spruce lamella | Biological  Durability                  | EN350-2                | Class 1     |
| DETAIL DESCRIPTION Backside  |   | Backside material    | Veneer              |   |                        | Camaliant   |
| All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be |   |                      | 15 mm               | CARB2 Slipperiness CEN/TS15676          |                        | Compliant   |
|  |   | Installation method  | Glue-down, Floating |   |                        | IVI D       |

## **COLOUR CHANGE**

present in all sizes and numbers.

Some muting of colour variation to medium, straw brown.

## Other products in this collection



#### CERTIFICATES



### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.