



OAK ROCCIA

DDODLICT DETAIL C

This oiled, 2-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from foggy grey to wet sand hues to create a dramatic and weathered look. The knots and cracks in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	152XDDEKGGKW195 / 7393969045414	range
Design / Wood Species	2-strip / Oak	Warranty
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIE
Natural/Stained		Moisture content
Design features	Brushed, Saw marks	— Minimun Mean Density
Width x Length x Thickness	190 x 1900 x 15 mm	— kg/m ³
Weight per package / per	19 kg / 8.64 kg	Reaction To Fire
m2		Formaldehyde Emission
Area per package / per	2.2 m ² / 76 m ²	Content PCP
pallet		Breaking Strength N/mm ²
Grading	Expressive	— Thermal Conductivity
Joint	Woodloc® 5G	Biological Durability
Installation method	Glue-down, Floating	— CARB2
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	Slip resistance
thickness		PRISONED DAME LAM PREPRENT
Resandable	2-4 times	CARB P2
Core material	Pine/Spruce lamella	Compliant Sylvw 9
Backside material	Veneer	

PRODU	JCT [DETAI	LS
-------	-------	-------	----

riarariess (Bririell) value /	3,7 7 2.2 3.3	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

3.7 / 2.2 - 5.9











DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE