



OAK DECORUM

This honey-hued 2-strip floor from the Da Capo Collection features charcoal knots and cracks for a richly rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the aged appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) valu	
Article Number / EAN Code	152XDDEKFNKW195 / 7393969045384	range	
Design / Wood Species	2-strip / Oak	Warranty	
Surface treatment /	Oil / Natural	TECHNICAL PROPER	
Natural/Stained		Moisture content	
Design features	Bevelled 4-sided, Brushed, Handscraped	— Minimun Mean Densit	
Width x Length x Thickness	190 x 1900 x 15 mm	— kg/m³	
Weight per package / per	19 kg / 8.64 kg	Reaction To Fire	
<u>m2</u>		— Formaldehyde Emissic	
Area per package / per	2.17 m ² / 75.95 m ²	Content PCP	
pallet		Breaking Strength N/m	
Grading	Expressive	— Thermal Conductivity	
Joint	Woodloc® 5G	Biological Durability	
Installation method	Floating, Glue-down	— CARB2	
Floor heating	Yes		
Wear leayer material /	Hardwood / 3.5 mm	Slip resistance	
thickness		TSCA LANGSION CLARGE	
Resandable	2-4 times	CARB P2	
Core material	Pine/Spruce	Compliant 092VW 044	
Backside material	Veneer		

PROD	UCT D	ETAILS

Hardness (Brinell) value /	3,//2.2 - 5.9
range	
Warranty	30 years

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE