



OAK DOMO

The deep golden brown hues found in this smoked 2-strip floor from the Da Capo Collection highlight its rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES				
Article Number	152XDDEKFPKW195	Wood Species	Oak	Moisture content	EN13183	7%±2%		
EAN Code	7393969045391	Design	2-strip	Minimum Mean Density kg/m³ >500 kg/m³				
Surface treatment	Oil This floor should be oiled immediately after installation.	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1		
		Range	Kährs Supreme					
		Collection	Da Capo Collection	Formaldehyde Emission	EN717-1	E1		
Design features	Bevelled 4-sided, Brushed, Smoked, Handscraped	Resandable	2-4 times	Content PCP	CEN/TR14823	≤ 5 ppm		
		Natural/Stained	Natural	Breaking Strength N/mm²	EN1533	NPD		
Dimensions	190 x 1900 mm	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK		
Weight per Package	19 kg	Joint	Woodloc® 5G					
Area per Package	2.2 m²	Floor heating	Yes	Thermal Resistance R-Value .11 (m2K/W)				
Package info	Packages may contain start and stop boards.	Warranty	30 years	Biological Durability	EN350-2	Class 1		
		Warranty US	25 years	CARB2 Compliant				
DETAIL DESCRIPTION	All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.	Wear-layer material	Hardwood	Slipperiness	CEN/TS15676	NPD		
		Wear Layer Thickness	3.5 mm					
		Core material	Pine/Spruce lamella					
		Backside material	Veneer					
		Thickness	15 mm					
		Installation method	Floating, Glue-down					
		Surface Colour	Brown FK					

COLOUR CHANGE

Smoked product - noticable color change over time.

Other products in this collection



Oak Indietro



Oak Decorum



Oak Domo



Oak Dussato



Oak Unico



Oak Sparuto



Oak Indossati



Oak Maggiore

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.