



## **OAK MAGGIORE**

The black-and-tan colour range in this single-strip floor from the Da Capo Collection results in an extremely rustic expression. The naturally occurring knots and cracks add to the quality of the surface, giving the floor a worn complexion reminiscent of reclaimed timber. Each board is carefully brushed to bring out the quality of the grain and highlight the natural properties of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	151XDDEKF0KW195 / 7393969045438	range		
Design / Wood Species	Plank / Oak	Warranty	30 years	
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES		
Natural/Stained		Moisture content		70/ + 20/
Design features	Handscraped, Bevelled 4-sided, Brushed		EN13183	7%±2%
Width x Length x Thickness	190 x 1900 x 15 mm	— Minimun Mean Density — kg/m³		>500 kg/m³
Weight per package / per	19 kg / 8.64 kg	Reaction To Fire	EN13501-1	Dfl-s1
m2		— Formaldehyde Emission	EN717-1	E1
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	Content PCP	CEN/TR14823	≤ 5 ppm
pallet		Breaking Strength N/mm²	EN1533	NPD
Grading	Expressive	— Thermal Conductivity	EN12664	0,11W/mK
Joint	Woodloc® 5G			
Installation method	Glue-down, Floating	Biological Durability	EN350-2	Class 1
Floor heating	Yes	— CARB2		Compliant
Wear leayer material /	Hardwood / 3.5 mm	Slip resistance	CEN/TS15676	NPD
thickness		TSCA UNISSION CLASS	(PHISSONG DANG LINE RYTERBOOK)	
Resandable	2-4 times	CARB P2		
Core material	Pine/Spruce	Compliant STYN ON BASI	Α	
Backside material	Veneer			

## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

## Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE