



OAK MAGGIORE

The black-and-tan colour range in this single-strip floor from the Da Capo Collection results in an extremely rustic expression. The naturally occurring knots and cracks add to the quality of the surface, giving the floor a worn complexion reminiscent of reclaimed timber. Each board is carefully brushed to bring out the quality of the grain and highlight the natural properties of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged appearance of the floor.

| PRODUCT DETAILS | | PRODUCT DETAILS | | |
|-----------------------------|--|-----------------------------------|---------------------------------------|------------|
| Product type / Construction | Wood Floors / 3-layer parquet | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| Article Number / EAN Code | 151XDDEKF0KW195 / 7393969045438 | range | | |
| Design / Wood Species | 1-strip / Oak | Warranty | 30 years | |
| Surface treatment / | Oil / Stained | TECHNICAL PROPERTIES | | |
| Natural/Stained | | Moisture content | EN13183 | 7%±2% |
| Design features | Handscraped, Bevelled 4-sided, Brushed | | ENIDIOD | |
| Width x Length x Thickness | 190 x 1900 x 15 mm | — Minimun Mean Density — kg/m³ | | >500 kg/m³ |
| Weight per package / per | 19 kg / 8.64 kg | Reaction To Fire | EN13501-1 | Dfl-s1 |
| m2 | | — Formaldehyde Emission | EN717-1 | E1 |
| Area per package / per | 2.17 m ² / 75.95 m ² | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| pallet | | Breaking Strength N/mm² | FN1533 | NPD |
| Grading | Expressive | — Thermal Conductivity | EN12664 | 0.11W/mK |
| Joint | Woodloc® 5G | Biological Durability | EN350-2 | Class 1 |
| Installation method | Glue-down, Floating | | LN330-2 | |
| Floor heating | Yes | CARB2 | CENTRAL CAL | Compliant |
| Wear leayer material / | Hardwood / 3.5 mm | Slip resistance | CEN/TS15676 | NPD |
| thickness | | TSCA UNICON CLASS | (Spressioned damed Lyang représedure) | |
| Resandable | 2-4 times | CARB P2 | | |
| Core material | Pine/Spruce lamella | Compliant Oslew on BASIA | | |
| Backside material | Veneer | | | |

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE