



## MATTERHORN CLICK 5 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Til	es and Planks / Click SPC LVT	Colour fastness	EN ISO 105-B02	≥ 6
Article Number / EAN Code	LTCLS3004-300-5 / 7393969113052		Slip resistance	EN 13893	DS (>0.3)
Design	Tile Design		Slip resistance	DIN 51130	R10
Width x Length x Thickness	300 x 600 x 5 mm		Statical electrical	EN 1815	< 2 kV (antistatic)
Weight per package / per	16.8 kg / 7.64 kg		propensity		
m2			Scratch resistance	EN16094	Pass with good results
Area per package / per	2.16 m <sup>2</sup> / 103.68 m <sup>2</sup>		Chemical resistance	EN ISO 26987	Pass with good results
pallet			Effect of castor chair	EN 425	Suitable
Joint	Click5G		Resistance to bacteria and		Good
Installation method	Floating		fungi		
Floor heating	Yes		Impact sound reduction	EN ISO 10140	20 <b>∆</b> Lw dB (IXPE
Wear leayer thickness	0.3 mm		_		underlayment)
Warranty	10 years		_		
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1	<del>_</del>		
Thermal Resistance R-Value		0.032 (m2K/W)	_		
Residual indentation EN ISO		< 0.2 mm (*with	<del>_</del>		
24343-1		underlayment)			
Dimensional stability	EN ISO 23999	< 0.1 %	<del>_</del>		

## Other products in this collection







MAKALU CLICK



STEELE CLICK 5 MM



MATTERHORN CLICK