

MATTERHORN CLS 300-5

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Vinyl Flooring / Click SPC LVT	Slip resistance	EN 13893	DS (>0.3)
Article Number / EAN Code	LTCLS3004-300-5 / 7393969113052	Slip resistance	DIN 51130	R10
Design	Tile Design	Statical electrical	EN 1815	< 2 kV (antistatic)
Width x Length x Thickness	11 3/4 x 23 5/8 x 1/4"	propensity		
Weight per package / per	37 lbs / 16.8 lbs	Scratch resistance	EN16094	Pass with good results
m2		Chemical resistance	EN ISO 26987	Pass with good results
Area per package / per	23.3 sqft / 1116 sqft	Effect of castor chair	EN 425	Suitable
pallet		Resistance to bacteria and		Good
Joint	Click5G	fungi		
Installation method	Floating	Impact sound reduction	EN ISO 10140	20 ∆ Lw dB (IXPE
Floor heating	Yes			underlayment)
Wear leayer thickness	0"			
TECHNICAL PROPERTIES				

TECHNICAL PROPERTIES				
Reaction To Fire	EN13501-1	Bfl-s1		
Thermal Resistance R-Value		0.032 (m2K/W)		
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with		
		underlayment)		
Dimensional stability	EN ISO 23999	< 0.1 %		
Colour fastness	EN ISO 105-B02	≥ 6		

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Schwarzhorn - Click 5 mm



Steele - Click 5 mm



Matterhorn - Click 5 mm