



Pass with good results

Pass with good results

Suitable

20 **∆**Lw dB (IXPE

underlayment)

Good

EN16094

EN 425

EN ISO 26987

EN ISO 10140


MATTERHORN CLS 300-5

PRODUCT DETAILS			TECHNICAL PROPERTIES
Construction	Click 5 mm		Scratch resistance
Article Number / EAN Code	LTCLS3004-300-5 / 7393969113052		Chemical resistance
Design	Stone design		Effect of castor chair
Width x Length x Thickness	11 3/4 x 23 5/8 x 1/4"		Resistance to bacteria and
Weight per package / per	37 lbs / 16.8 lbs		fungi
m2			Impact sound reduction
Area per package / per	23.7 sqft / 1115.1 sqft		
pallet			
Wear leayer thickness	0"		
TECHNICAL PROPERTIES			
Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.032 (m2K/W)	
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with	
		underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	

Descriptions & Imagery

Other products in this collection







Makalu - Click 5 mm



Steele - Click 5 mm



Matterhorn - Click 5 mm