



STEELE CLICK 5 MM

The Kährs Luxury Vinyl Plank floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The LVP floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Vinyl Plank floors, they are phthalate-free.

| PRODUCT DETAILS | | | TECHNICAL PROPERTIES | | |
|-----------------------------|---------------------------------|-----------------|----------------------------|--------------|-------------------------|
| Product type / Construction | Vinyl Flooring / Click SPC LVT | | Slip resistance | EN 13893 | DS (>0.3) |
| Article Number / EAN Code | LTCLS3006-300-5 / 7393969113045 | | Slip resistance | DIN 51130 | R10 |
| Design | Tile Design | | Statical electrical | EN 1815 | < 2 kV (antistatic) |
| Width x Length x Thickness | 11 3/4 x 23 5/8 x 1/4" | | propensity | | |
| Weight per package / per | 37 lbs / 16.8 lbs | | Scratch resistance | EN16094 | Pass with good results |
| m2 | | | Chemical resistance | EN ISO 26987 | Pass with good results |
| Area per package / per | 23.3 sqft / 1116 sqft | | Effect of castor chair | EN 425 | Suitable |
| pallet | | | Resistance to bacteria and | | Good |
| Joint | Click5G | | fungi | | |
| Installation method | Floating | | Impact sound reduction | EN ISO 10140 | 20 ∆ Lw dB (IXPE |
| Floor heating | Yes | | | | underlayment) |
| Wear leayer thickness | 0" | | | | |
| TECHNICAL PROPERTIES | | | | | |
| Reaction To Fire | EN13501-1 | Bfl-s1 | | | |
| Thermal Resistance R-Value | | 0.032 (m2K/W) | | | |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with | | | |
| | | underlayment) | | | |
| Dimensional stability | EN ISO 23999 | < 0.1 % | | | |
| Colour fastness | EN ISO 105-B02 | ≥ 6 | | | |

Other products in this collection







STEELE CLICK 5 MM



MATTERHORN CLICK