




STEELE CLS 300-5

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Vinyl Flooring / Click SPC LVT		Slip resistance	EN 13893	DS (>0.3)
Article Number / EAN Code	LTCLS3006-300-5 / 7393969113045		Slip resistance	DIN 51130	R10
Design	Tile Design		Statical electrical	EN 1815	< 2 kV (antistatic)
Width x Length x Thickness	11 3/4 x 23 5/8 x 1/4"		propensity		
Weight per package / per	37 lbs / 16.8 lbs		Scratch resistance	EN16094	Pass with good results
m2			Chemical resistance	EN ISO 26987	Pass with good results
Area per package / per	23.3 sqft / 1116 sqft		Effect of castor chair	EN 425	Suitable
pallet			Resistance to bacteria and		Good
Joint	Click5G		fungi		
Installation method	Floating		Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
Floor heating	Yes				underlayment)
Wear leayer thickness	0"				
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1			
Thermal Resistance R-Value		0.032 (m2K/W)			
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with			
		underlayment)			
Dimensional stability	EN ISO 23999	< 0.1 %			
Colour fastness	EN ISO 105-B02	≥ 6			

Other products in this collection







Steele - Click 5 mm



Matterhorn - Click 5 mm