



OAK RITORNO

This oiled, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from foggy grey to wet sand hues to create a dramatic and weathered look. The knots, cracks and discolourations in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--|---|----------------------|---------------------|--------------------------------|-------------|------------------------|
| Article Number | 153XCDEKGGKW195 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969045469 | Design | 3-strip | content | | |
| Surface Treatment | Oil This floor should be oiled immediately after installation. | Grading | Expressive | Minimun Mean Density kg/m | | >500 kg/m ³ |
| | | Range | Kährs Supreme | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Collection | Da Capo Collection | Formaldehyde | EN717-1 | E1 |
| Refining Treatment | Brushed, Saw marks | Natural/Stained | Stained | Emission | | |
| Dimensions | 190 x 1900 mm | Brinell Value | 3,7 | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Weight per Package | 19 kg | Joint | Woodloc® 5G | Breaking EN1533 Strength N/mm² | EN1533 | NPD |
| Area per Package | 2.2 m ² | Floor heating | Yes | | | |
| Area per pallet | 76 m² | | 25 years | Thermal | EN12664 | 0,14 W/mK |
| Package info | Packages may contain start and stop boards. | Wear-layer material | Hardwood | Conductivity | | |
| | | Wear Layer Thickness | 3.5 mm | Thermal Resistance R-Value | | .11 (m2K/W) |
| DETAIL DESCRIPTION | | Core material | Pine/Spruce lamella | Biological Durability | EN350-2 | Class 1 |
| All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | Backside material | Veneer | CARB2 | | Compliant |
| | | | 15 mm | Slipperiness | CEN/TS15676 | ' |
| | | Installation method | Glue-down, Floating | | CEIW1515070 | 0 |
| | | Surface Colour | Grey | | | |

COLOUR CHANGE

Stained product - noticeable color change over time.

Other products in this collection



CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.