



OAK UNICO

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	151XDDEKFPKW195 / 7393969045452	range
Design / Wood Species	1-strip / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIES
Natural/Stained		Moisture content
Design features	Bevelled 4-sided, Brushed, Smoked,	Minimun Mean Density
	Handscraped, Wooden plugs	— kg/m ³
Width x Length x Thickness	190 x 1900 x 15 mm	— Reaction To Fire
Weight per package / per	19 kg / 8.64 kg	Formaldehyde Emission
m2		
Area per package / per	2.17 m ² / 75.95 m ²	Content PCP
pallet		Breaking Strength N/mm ²
Grading	Expressive	Thermal Conductivity
Joint	Woodloc® 5G	Biological Durability
Installation method	Glue-down, Floating	CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 3.5 mm	TSCA "YESION CZ 45.
thickness	Haraweda / 3.5 Hill	TITLE VI
Resandable	2-4 times	Compliant English BASTA
Core material	Pine/Spruce lamella	
Backside material	Veneer	

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE