



Da Capo Collection



## OAK UNICO

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

### PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	151XDDEKFPKW195 / 7393969045452
Design / Wood Species	1-strip / Oak
Surface treatment / Natural/Stained	Oil / Natural
Design features	Bevelled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs
Width x Length x Thickness	190 x 1900 x 15 mm
Weight per package / per m <sup>2</sup>	19 kg / 8.64 kg
Area per package / per pallet	2.2 m <sup>2</sup> / 76 m <sup>2</sup>
Grading	Expressive
Joint	Woodloc® 5G
Installation method	Glue-down, Floating
Floor heating	Yes
Wear layer material / thickness	Hardwood / 3.5 mm
Resandable	2-4 times
Core material	Pine/Spruce lamella
Backside material	Veneer

### PRODUCT DETAILS

Brinell value / range	3,7 / 2.2 - 5.9
Warranty	30 years

### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m <sup>2</sup> K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



### DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** Smoked product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2024-07-17

1 (2)


Other products in this collection



Oak Indietro



Oak Decorum




Oak Domo




Oak Dussato



Oak Unico



Oak Sparuto



Oak Indossati



Oak Maggiore