



OAK UNICO

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

PRODUCT DETAILS

| | |
|-----------------------------------------|--------------------------------------------------------------|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 151XDDEKFPKW195 / 7393969045452 |
| Design / Wood Species | 1-strip / Oak |
| Surface Treatment / Natural/Stained | Oil / Natural |
| Refining Treatment | Bevelled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs |
| Width x Length x Thickness | 190 x 1900 x 15 mm |
| Weight per package / per m ² | 19 kg / 8.64 kg |
| Area per package / per pallet | 2.17 m ² / 75.95 m ² |
| Grading | Expressive |
| Joint | Woodloc® 5G |
| Installation method | Glue-down, Floating |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Core material | Pine/Spruce |
| Backside material | Veneer |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | | |
|-------------------------------------|------------------------|--------------------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | >500 kg/m ³ | |
| kg/m ³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticeable color change over time.


Packages may contain start and stop boards.

Descriptions & Imagery


All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2026-04-02

Other products in this collection



OAK DECORUM




OAK DOMO




OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE