



OAK UNICO

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

PRODUCT DETAILS

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151XDDEKFPKW195 / 7393969045452	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Natural	
Natural/Stained		
Refining Treatment	Bevelled 4-sided, Brushed, Smoked,	
	Handscraped, Wooden plugs	
Width x Length x Thickness	190 x 1900 x 15 mm	
Weight per package / per	19 kg / 8.64 kg	
m2		
Area per package / per	2.17 m ² / 75.95 m ²	
pallet		
Grading	Expressive	
Joint	Woodloc® 5G	
Installation method	Glue-down, Floating	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Core material	Pine/Spruce	
Backside material	Veneer	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD

EN350-2

CEN/TS15676



Slip resistance

CARB2

Biological Durability





DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

Class 1

NPD

Compliant

Other products in this collection



OAK DECORUM



OAK DOMO



OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE