



UNICO

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|---|---|----------------------|---------------------|---------------------------------------|-------------|-------------|
| Article Number | 151XDDEKFPKW195 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| EAN Code | 7393969045452 | Design | 1-strip | Minimum Mean Density kg/m³ >500 kg/m³ | | |
| Surface Treatment | Oil This floor should be oiled immediately after installation. | Grading | Expressive | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Range | Kährs Supreme | Formaldehyde Emission | EN717-1 | E1 |
| | | Collection | Da Capo Collection | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Refining Treatment | Bevelled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs | Natural/Stained | Natural | Breaking Strength N/mm² | EN1533 | NPD |
| | | Brinell Value | 3,7 | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Dimensions | 190 x 1900 mm | Joint | Woodloc® 5G | Thermal Resistance R-Value | .11 (m2K/W) | |
| Weight per Package | 19 kg | Floor heating | Yes | Biological Durability | EN350-2 | Class 1 |
| Area per Package | 2.2 m² | | 25 years | CARB2 | Compliant | |
| Area per pallet | 76 m² | Wear-layer material | Hardwood | Slipperiness | CEN/TS15676 | NPD |
| Package info | Packages may contain start and stop boards. | Wear Layer Thickness | 3.5 mm | | | |
| | | Core material | Pine/Spruce lamella | | | |
| | | Backside material | Veneer | | | |
| DETAIL DESCRIPTION | | | 15 mm | | | |
| | | Installation method | Glue-down, Floating | | | |
| All naturally occuring wood colour variations | | | | | | |

COLOUR CHANGE

Smoked product - noticeable color change over time.

Other products in this collection



Decorum



Domo



Dussato



Unico



Sparuto



Indossati



Maggiore

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.