



OAK INDOSSATI

DDODLICT DETAIL C

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7
Article Number / EAN Code	151XDDEKFHKW195 / 7393969045421	range	
Design / Wood Species	Plank / Oak	Warranty	30
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES	
Natural/Stained		— Moisture content	EN
Design features	Bevelled 4-sided, Brushed, Light smoked,	Minimun Mean Density	
	Handscraped	— kg/m ³	
Width x Length x Thickness	190 x 1900 x 15 mm	— Reaction To Fire	EN
Weight per package / per	19 kg / 8.64 kg	Formaldehyde Emission	EN
m2		— Content PCP	CE
Area per package / per	2.17 m ² / 75.95 m ²	Breaking Strength N/mm²	EN
pallet		Thermal Conductivity	EN
Grading	Expressive		
Joint	Woodloc® 5G	Biological Durability	EN
Installation method	Glue-down, Floating	— CARB2	
Floor heating	Yes	Slip resistance	CE
Wear leayer material /	Hardwood / 3.5 mm	TSCA UNESION CLASS	
thickness		CARB P2	(
Resandable	2-4 times	Compliant SALYW ONLY BASIA	A
Core material	Pine/Spruce		
Backside material	Veneer		

DDODLICT DETAIL C

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	_
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE