



## OAK INDOSSATI

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor.

### PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	151XDDEKFHKW195 / 7393969045421
Design / Wood Species	Plank / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Bevelled 4-sided, Brushed, Light smoked, Handscraped
Width x Length x Thickness	190 x 1900 x 15 mm
Weight per package / per m2	19 kg / 8.64 kg
Area per package / per pallet	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>
Grading	Expressive
Joint	Woodloc® 5G
Installation method	Glue-down, Floating
Floor heating	Yes
Wear layer material / thickness	Hardwood / 3.5 mm
Resandable	2-4 times
Core material	Pine/Spruce
Backside material	Veneer

### PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years
<b>TECHNICAL PROPERTIES</b>	
Moisture content	EN13183 7%±2%
Minimun Mean Density kg/m <sup>3</sup>	>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1 Dfl-s1
Formaldehyde Emission	EN717-1 E1
Content PCP	CEN/TR14823 ≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533 NPD
Thermal Conductivity	EN12664 0,11W/mK
Biological Durability	EN350-2 Class 1
CARB2	Compliant
Slip resistance	CEN/TS15676 NPD



### DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** Stained product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection



OAK INDIETRO



OAK DECORUM



OAK DOMO



OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE