



OAK INDOSSATI

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor

PRODUCT DETAILS

Article Number	151XDDEKFHKW195
EAN Code	7393969045421
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Brushed, Light smoked, Handscraped
Dimensions	190 x 1900 mm
Weight per Package	19 kg
Area per Package	2.2 m ²
Area per pallet	76 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

Wood Species	Oak
Design	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Da Capo Collection
Resandable	2-4 times
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc® 5G
Floor heating	Yes
Warranty	30 years
Warranty US	25 years
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce lamella
Backside material	Veneer
Thickness	15 mm
Installation method	Glue-down, Floating
Surface Colour	White FH

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m ³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Oak Indietro



Oak Decorum



Oak Domo



Oak Dussato



Oak Unico



Oak Sparuto



Oak Indossati



Oak Maggiore

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.