



INDOSSATI

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor

PRODUCT DETAILS

| | |
|---|--|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 151XDDEKFKHW195 / 7393969045421 |
| Design / Wood Species | 1-strip / Oak |
| Surface Treatment / Natural/Stained | Oil / Stained |
| Refining Treatment | Bevelled 4-sided, Brushed, Light smoked, Handscraped |
| Width x Length x Thickness | 190 x 1900 x 15 mm |
| Weight per package / per m ² | 19 kg / 8.64 kg |
| Area per package / per pallet | 2.2 m ² / 76 m ² |
| Grading | Expressive |
| Joint | Woodloc® 5G |
| Installation method | Glue-down, Floating |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Veneer |
| Brinell value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | | |
|-------------------------------------|------------------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.


Packages may contain start and stop boards.

Descriptions & Imagery


All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2024-07-23

Other products in this collection



Decorum




Domo




Dussato



Unico



Sparuto



Indossati



Maggiore