



# **INDOSSATI**

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor

| PRODUCT DETAILS                                                                                 |                                                                         | FACTS                |                     | TECHNICAL PROPERTIES                   |              |                        |
|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------|---------------------|----------------------------------------|--------------|------------------------|
| Article Number                                                                                  | 151XDDEKFHKW195                                                         | Wood Species         | Oak                 | Moisture                               | EN13183      | 7%±2%                  |
| EAN Code                                                                                        | 7393969045421                                                           | Design               | 1-strip             | content                                |              |                        |
| Surface Treatment                                                                               | Oil<br>This floor should be oiled<br>immediately after<br>installation. | Grading              | Expressive          | Minimun Mean Density kg/m <sup>3</sup> |              | >500 kg/m <sup>3</sup> |
|                                                                                                 |                                                                         | Range                | Kährs Supreme       | Reaction To<br>Fire                    | EN13501-1    | Dfl-s1                 |
|                                                                                                 |                                                                         | Collection           | Da Capo Collection  | Formaldehyde<br>Emission               | EN717-1      | E1                     |
| Refining Treatment                                                                              | Bevelled 4-sided,<br>Brushed, Light smoked,<br>Handscraped              | Natural/Stained      | Stained             |                                        |              |                        |
|                                                                                                 |                                                                         | Brinell Value        | 3,7                 | Content PCP                            | CEN/TR14823  | ≤ 5 x 10-6n            |
| Dimensions                                                                                      | 190 x 1900 mm                                                           | Joint                | Woodloc® 5G         | Breaking Strength N/mm²                | EN1533       | NPD                    |
| Weight per Package                                                                              | 19 kg                                                                   | Floor heating        | Yes                 |                                        |              |                        |
| Area per Package                                                                                | 2.2 m <sup>2</sup>                                                      |                      | 25 years            | Thermal                                | EN12664      | 0,14 W/mK              |
| Area per pallet                                                                                 | 76 m²                                                                   | Wear-layer material  | Hardwood            | Conductivity                           |              |                        |
| Package info                                                                                    | Packages may contain start and stop boards.                             | Wear Layer Thickness | 3.5 mm              | Thermal Resistance R-Value             |              | .11 (m2K/W)            |
|                                                                                                 |                                                                         | Core material        | Pine/Spruce lamella | Biological  Durability                 | EN350-2      | Class 1                |
| DETAIL DESCRIPTION                                                                              |                                                                         | Backside material    | Veneer              | CARB2                                  |              | Compliant              |
| All naturally occuring wood colour variations                                                   |                                                                         |                      | 15 mm               | Slipperiness                           | CEN/TS15676  | '                      |
| allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and |                                                                         | Installation method  | Glue-down, Floating | Suppermess                             | CLIW 1313070 | 141.0                  |

#### **COLOUR CHANGE**

Stained product - noticable color change over time.

black knots and cracks. Knots and cracks will be

present in all sizes and numbers.

## Other products in this collection



### CERTIFICATES



## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.