



## OAK INDOSSATI

The white stain on this light smoked, single-strip floor from the Da Capo Collection highlights its rustic expression. The naturally occurring semi-filled knots and cracks combined with occasionally occurring distress marks add to the quality of the surface, giving the floor a worn appearance reminiscent of reclaimed timber. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged complexion of the floor

nell) value / 3,7 / 2.2 -
25 years
PROPERTIES
tent EN13183
n Density
ire EN13501-
e Emission EN717-1
CEN/TR14
ngth N/mm² EN1533
stance R-Value
ability EN350-2
-
e CEN/TS15
JON CLASE
SAM Ogs.
r

PRODU	ICT DE	ETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	25 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## **Descriptions & Imagery**

