



MAKALU CLS 300-5

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

Р	RC	DI	JCT	DF	ΓΑΙ	١ς

Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT
Article Number / EAN Code	LTCLS3007-300-5 / 7393969113038
Design	Tile Design
Width x Length x Thickness	300 x 600 x 5 mm
Weight per package / per	16.8 kg / 7.64 kg
m2	
Area per package / per	2.2 m ² / 103.6 m ²
pallet	
Joint	Click5G
Installation method	Floating
Floor heating	Yes
Wear leayer thickness	0.3 mm

TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.032 (m2K/W)	
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with	
		underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	

TECHNICAL PROPERTIES

Slip resistance DIN 51130 R10 Statical electrical EN 1815 < 2 kV (antistatic) propensity
- · · · (- · · · · · · · · · · · · · · ·
nronensity
properiors
Scratch resistance EN16094 Pass with good results
Chemical resistance EN ISO 26987 Pass with good results
Resistance to bacteria and Good
fungi
Impact sound reduction EN ISO 10140 20 ΔLw dB (IXPE
underlayment)







Other products in this collection







STEELE - CLICK 5 MM



MATTERHORN - CLICK 5 MM