



## OAK DUSSATO

The white oiled surface of this smoked, 2-strip floor from the Da Capo Collection brings out the rustic characteristics in the timber. This beautifully aged effect is prominent and provides a balanced contrast to the lighter finish. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	152XDDEKFHKW195 / 7393969045407	range		
Design / Wood Species	2-strip / Oak	Warranty	30 years	
Surface treatment / Natural/Stained	Oil / Stained	TECHNICAL PROPERTIES	S	
	Developed A side of Developed Liebt constant	— Moisture content	EN13183	7%±2%
Design features	Bevelled 4-sided, Brushed, Light smoked, Handscraped	Minimun Mean Density —— kg/m³		>500 kg/m³
Width x Length x Thickness	190 x 1900 x 15 mm	— Reaction To Fire	EN13501-1	Dfl-s1
Weight per package / per	19 kg / 8.64 kg	Formaldehyde Emission	EN717-1	E1
<u>m2</u>		Content PCP	CEN/TR14823	≤ 5 ppm
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
pallet		— Thermal Conductivity	EN12664	0,11W/mK
Grading	Expressive	Biological Durability	EN350-2	Class 1
Joint	Woodloc® 5G	— CARB2	E11330 Z	Compliant
Installation method	Floating, Glue-down		CEN/TC1E676	
Floor heating	Yes	Slip resistance	CEN/TS15676	NPD
Wear leayer material /	Hardwood / 3.5 mm	TSCA UMSSION CLASS	(Dressoors dans lake entéreque)	
thickness		CARB P2		
Resandable	2-4 times	Compliant Salve of BASI	A	
Core material	Pine/Spruce			
Backside material	Veneer	<u> </u>		

## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | <sup>©</sup>Kährs 2025-11-26

## Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE