

## OAK DUSSATO

The white oiled surface of this smoked, 2-strip floor from the Da Capo Collection brings out the rustic characteristics in the timber. This beautifully aged effect is prominent and provides a balanced contrast to the lighter finish. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	152XDDEKFHKW195 / 7393969045407	range		
Design / Wood Species	2-strip / Oak	Warranty	30 years	
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES	-	
Natural/Stained		— Moisture content	FN13183	7%±2%
Design features	Bevelled 4-sided, Brushed, Light smoked,	Minimun Mean Density	EN13183	>500 kg/m <sup>3</sup>
	Handscraped	— kg/m³		0
Width x Length x Thickness	190 x 1900 x 15 mm	— Reaction To Fire	EN13501-1	Dfl-s1
Weight per package / per	19 kg / 8.64 kg	Formaldehyde Emission	EN717-1	E1
m2		- Content PCP	CFN/TR14823	≤ 5 ppm
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
pallet		— Thermal Conductivity	EN12664	0,11W/mK
Grading	Expressive	— Biological Durability	EN350-2	Class 1
Joint	Woodloc® 5G	— CARB2	LINUSU Z	Compliant
Installation method	Floating, Glue-down	-	CEN/TS15676	NPD
Floor heating	Yes	Slip resistance	CEIN/1313070	NPD
Wear leayer material /	Hardwood / 3.5 mm	TSCA UN <sup>65510N CL</sup> YB	(Pressone) David Laure Intereury	
thickness				
Resandable	2-4 times	Compliant AND BASI	A	
Core material	Pine/Spruce lamella			
Backside material	Veneer			

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Descriptions & Imagery

www.kahrs.com | <sup>©</sup>Kährs 2025-08-13

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection





OAK DECORUM

OAK SPARUTO





OAK DOMO





OAK INDOSSATI



OAK DUSSATO



OAK MAGGIORE

OAK UNICO