



DUSSATO

The white oiled surface of this smoked, 2-strip floor from the Da Capo Collection brings out the rustic characteristics in the timber. This beautifully aged effect is prominent and provides a balanced contrast to the lighter finish. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor.

| PRODUCT DETAILS | |
|--------------------|---|
| Article Number | 152XDDEKFHKW195 |
| EAN Code | 7393969045407 |
| Surface Treatment | Oil This floor should be oiled immediately after installation. |
| Refining Treatment | Bevelled 4-sided, Brushed, Light smoked, Handscraped |
| Dimensions | 190 x 1900 mm |
| Weight per Package | 19 kg |
| Area per Package | 2.2 m ² |
| Package info | Packages may contain start and stop boards. |

| DETAIL DESCRIPTION | |
|---|--|
| All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | |

| COLOUR CHANGE | |
|--|--|
| Stained product - noticeable color change over time. | |

| FACTS | |
|----------------------|---------------------|
| Wood Species | Oak |
| Design | 2-strip |
| Grading | Expressive |
| Range | Kährs Supreme |
| Collection | Da Capo Collection |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5G |
| Floor heating | Yes |
| | 25 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Veneer |
| | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | White |

| TECHNICAL PROPERTIES | | |
|--|------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m ³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |

Other products in this collection



Decorum



Domo



Dussato



Unico



Sparuto



Indossati



Maggiore

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.