



OAK SPARUTO

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Foursided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	151XDDEKFRKW195 / 7393969045445	range
Design / Wood Species	Plank / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNICAL PROPERTI
Natural/Stained		Moisture content
Design features	Bevelled 4-sided, Brushed, Smoked,	Minimun Mean Density
	Handscraped, Wooden plugs	
Width x Length x Thickness	190 x 1900 x 15 mm	Reaction To Fire
Weight per package / per	19 kg / 8.64 kg	Formaldehyde Emission
m2		
Area per package / per	2.17 m ² / 75.95 m ²	Content PCP
pallet		Breaking Strength N/mm
Grading	Expressive	Thermal Conductivity
loint	Woodloc® 5G	Biological Durability
Installation method		CARB2
-	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	TITLE VI
thickness		CARB P2
Resandable	2-4 times	Compliant Strw ON DA
Core material	Pine/Spruce	
Backside material	Veneer	

Р	RO	Dl	JC	ΓD	EΤ	ΑI	LS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs 2025-09-15

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE