



SPARUTO

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

PRODUCT DETAILS

Article Number	151XDDEKFRKW195
EAN Code	7393969045445
Surface Treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs
Dimensions	190 x 1900 mm
Weight per Package	19 kg
Area per Package	2.2 m ²
Area per pallet	76 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Smoked product - noticeable color change over time.

FACTS

Wood Species	Oak
Design	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Da Capo Collection
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc® 5G
Floor heating	Yes
	25 years
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce lamella
Backside material	Veneer
Thickness	15 mm
Installation method	Floating, Glue-down

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m ³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m ² K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Oak Roccia



Oak Anziano




Oak Indietro



Oak Ritorno



Decorum



Domo




Dussato




Unico



Sparuto



Indossati



Maggiore

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.