



## OAK SPARUTO

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

### PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	151XDDEKFRKW195 / 7393969045445
Design / Wood Species	Plank / White Oak
Surface Treatment / Natural/Stained	Oil / Natural
Refining Treatment	Beveled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs
Width x Length x Thickness	7 1/2 x 74 3/4 x 5/8"
Weight per package / per m2	41.9 lbs / 19 lbs
Area per package / per pallet	23.4 sqft / 817.5 sqft
Grading	Expressive
Joint	Woodloc® 5G
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear layer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce
Backside material	Veneer

### PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	25 years

### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



### DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** Smoked product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |  
www.kahrs.com | ©Kährs,  
USA & Canada 2026-04-11

