



## SPARUTO

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

### PRODUCT DETAILS

<b>Article Number</b>	151XDDEKFRKW195
<b>EAN Code</b>	7393969045445
<b>Surface Treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Refining Treatment</b>	Beveled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs
<b>Dimensions</b>	7 1/2 x 74 3/4 "
<b>Weight per Package</b>	41.9 lbs
<b>Area per Package</b>	23.7 sqft
<b>Area per pallet</b>	818.1 sqft
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOR CHANGE

Smoked product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Expressive
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Da Capo Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Warranty</b>	25 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Backside material</b>	Veneer
<b>Thickness</b>	5/8"
<b>Installation method</b>	Floating, Glue-Down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>	>500 kg/m³	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m2K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slipperiness</b>	CEN/TS15676	NPD



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*