



OAK AURONZO

The warm ginger tones in this single-strip oak floor from the Rifugio Collection are enhanced by a natural oil finish, which highlights the charcoal knots and cracks. Each board is carefully brushed to bring out the character of the grain and emphasises the natural texture of the wood. Four-sided jagged bevelling at the edges and saw marks enhances the worn appearance of the floor.

PRODUCT DETAILS

| | |
|-------------------------------------|---|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 151XDDEKF9KW195 / 7393969046862 |
| Design / Wood Species | 1-strip / Oak |
| Surface treatment / Natural/Stained | Oil / Natural |
| Design features | Brushed, Saw marks, Broken bevelled 4-sided |
| Width x Length x Thickness | 190 x 1900 x 15 mm |
| Weight per package / per m2 | 16.7 kg / 7.59 kg |
| Area per package / per pallet | 2.2 m ² / 76 m ² |
| Grading | Dynamic |
| Joint | 5G |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce lamella |
| Brinell value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | | |
|-------------------------------------|------------------------|-----------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slip resistance | CEN/TS15676 | NPD |

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.


Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Oak Comici




Oak Pordoi



Oak Branca



Oak Locatelli



Oak Auronzo