



OAK AURONZO

The warm ginger tones in this single-strip oak floor from the Rifugio Collection are enhanced by a natural oil finish, which highlights the charcoal knots and cracks. Each board is carefully brushed to bring out the character of the grain and emphasises the natural texture of the wood. Four-sided jagged bevelling at the edges and saw marks enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet	Warranty	30 years
Article Number / EAN Code	151XDDEKF9KW195 / 7393969046862	TECHNICAL PROPERTIES	
Design / Wood Species	1-strip / Oak	Moisture content	EN13183 7%±2%
Surface Treatment / Natural/Stained	Oil / Natural	Minimum Mean Density	>500 kg/m ³
Refining Treatment	Brushed, Saw marks, Broken bevelled 4-sided	kg/m ³	
Width x Length x Thickness	190 x 1900 x 15 mm	Reaction To Fire	EN13501-1 Dfl-s1
Weight per package / per m2	16.7 kg / 7.59 kg	Formaldehyde Emission	EN717-1 E1
Area per package / per pallet	2.17 m ² / 75.95 m ²	Content PCP	CEN/TR14823 ≤ 5 x 10-6n
Grading	Dynamic	Breaking Strength N/mm ²	EN1533 NPD
Joint	Woodloc® 5G	Biological Durability	EN350-2 Class 1
Installation method	Floating, Glue-down	CARB2	Compliant
Floor heating	Yes	Slip resistance	CEN/TS15676 NPD
Wear layer material / thickness	Hardwood / 3.5 mm		
Resandable	2-3 times		
Core material	Pine/Spruce		
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9		

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection



OAK COMICI